

Spezifikation

Air Sea Containers Ltd.
Cavendish Street
Birkenhead
Merseyside
CH41 8FZ
England

Duttenhöfer T+L GmbH & Co. KG
Bahnhofstraße 100
67454 Haßloch / Deutschland

Ansprechpartner: Rafael Hinkel
E-Mail: Rafael.Hinkel@Duttenhoefer.com

+49 6324 590 128

+49 6324 590 119

Description: tight head poly composite drum					Volume [Liter]: 120		
Article:		Dated:		Ressource:		Dated: 15.03.2019	
Piece Weight [Kg]	Overrun volume [Liter]	Internal Diameter [mm]	Height [mm]	Steel thickness (mm)			
				Top	Lid	Wall	Bottom
14,3	121	450	815	1,0	--	1,0	1,0

Material:	DC01-A
Top:	Seamed
Lid:	--
Wall:	Welded, top retracted, 2 rolling hoops
Bottom:	Seamed
Embossing lid:	--
Embossing bottom:	UN 6HA1/X1.6/250/JJ – 1,0
Closure System:	2x 2" bung made of PP (Tri Sure) with wide threaded plug, on the top
Gasket lid:	--
Gasket(s) bung(s):	PE
Handle(s):	--
Internal coating:	--
Screen print:	--
Outside coating:	Blue RAL 5010
UN approval:	UN 6HA1/X1.6/250/Year/BAM5684-GDHS
Signing:	KA..... (order number)
Inliner:	Tight head inliner made of Lupolen ND450, 2000g, with groove
Delivery:	10 drums (2x5) on used CP1-pallet, cardboard between the two layers, shrink wrapped
Comments:	Bungs tighten by hand